

Model	Hyperparameter	Search Space	Sampler
Random Forest	Min_samples_split Min_samples_leaf	[2,4,8,16] [1,2,4]	Grid-Search
XGBoost	Learning rate Max_depth Reg_lambda Reg_alpha	(0.01,0.5) (2,12) (0,10) (0,10)	TPE
LSTM	Learning rate Batch size Hidden state dim. # Hidden layers Droprate	[0.001,0.005,0.01,0.05,0.1] [16,32,64,128] [16,32,64,128] [1,2,3] [0.0,0.2,0.5]	TPE
Meta-Model	Learning rate Batch size # Hidden layers Hidden state dim.	[0.001,0.005,0.01,0.05,0.1] [16,32,64,128] [0,1,2] [8,16,32]	Grid Search
Meta-Model+LSTM*	Lookback Window Learning rate Batch size # Hidden layers Hidden state dim. Learning rate* Hidden state dim.* # Hidden layers* Droprate*	[2,3,4] [0.001,0.005,0.01,0.05,0.1] [16,32,64,128] [0,1,2] [8,16,32] [0.001,0.005,0.01,0.05,0.1] [4,8,16,32] [1,2,3] [0.0,0.2,0.5]	TPE

Table S1: Hyperparameters for base models and meta-models. The brackets correspond to discrete values, while the parentheses correspond to continuous parameter ranges. Hyperparameters denoted by a star belong to the LSTM model. The lookback window refers to the metadata. Hyperparameters were either optimized by using a grid-search or with a tree-structured Parzen estimator from optuna. As the base model’s hyperparameters were tuned for each fitting window and dataset and the meta-model’s hyperparameter for each dataset, we did not provide the final choices.